

## RENDERS AND FINISHES



AVAILABLE IN BUCKETS OF 20L - YIELD PER BUCKET: 3 SQM FOR A THICKNESS OF 5 MM

## DESCRIPTION

**Canapulino** is a finish of lime putty aged 18 months and **Canapulo Fine 0-6** (hemp shiv) with the addition of Calcium Carbonates (natural colour) or Cocciopesto Powder or Coloured Earth (colour of your choice). Desalinating and dehumidifying thanks to its high hygroscopic capacity, it is an excellent humidity regulator on new and existing walls, guarantees maximum healthiness and significantly improves the comfort of the living spaces.

## APPLICATION

Ready-to-use and applied manually with a thickness of 5-10mm. Before application remove the existing plaster if damaged and make sure that the substrate is free of friable parts. Apply a first coat of Canapulo as a rough coat and then apply several coats up to reach the desired thickness, smooth and trowel.

Specific weight	1.110 kg/m <sup>3</sup>
Vapour permeability - $\mu$	4,5

## NOTE

Tecnocanapa's technical office is available for any support before, during and after the implementation phase.

The company is constantly improving and updating its product range.

Technical data, packaging and packing are therefore necessarily subject to change without notification.

Customers can always check with the company: technical data, documentation and samples.

For optimal use of our products, it is recommended to faithfully follow the instructions given in the Technical User Manual that is provided with the material or upon request.

Edition & Copyright • 01/2022