

RENDERS AND FINISHES

FINE MORTAR OF LIME PUTTY AND SAND

MALTA FINE DI GRASSELLO E SABBIA



AVAILABLE IN BAGS OF 25 KG

DESCRIPTION

Malta Fine is a ready-to-use smoothing compound composed of lime putty and classified sands.

USE

Malta Fine is a skim coat typically applied on base plasters such as 'Intonaco di **Intonaco di Calce Naturale** or **Bio Beton® 500 Venezia**. For internal use only.

SURFACE PREPARATION

The surface to be coated must be flat, coplanar and free of dust and dirt. Any traces of oils, greases, waxes, etc. must be removed beforehand. **Malta Fine** can be applied on a base plaster previously moistened.

PROCESSING

Apply with a metal trowel for a thickness of maximum 3 mm. After application, moisten and finish with a fine sponge float. It does not require mesh reinforcement.

STORAGE

If protected from frost, it has an unlimited duration.

TECHNICAL DATA

Specific weight - Kg/m ³ dry	ca. 1.700 kg/m ³
Granulometry	< 0,6 mm
Yield	ca. 3-4 kg/m ²
Maximum thickness of application	ca. 3 mm
Vapour permeability - EN 1015-19	$\mu \leq 9$ (measured value)
Water absorption by capillarity - EN 1015-18	W0
Thermal conductivity - EN 1745	$\lambda = 0,45$ W/m-K (table value)
Class - UNI EN 998-1	GP-CSI-W0