

FINE MORTAR OF LIME PUTTY AND SAND

MALTA

FINE DI GRASSELLO E SABBIA

AVAILABLE IN **25KG BAG**

DESCRIPTION

'Malta Fine' is a ready-to-use smoothing compound composed of lime putty and classified sands.

USE

'Malta Fine' is a skim coat typically applied on base plasters such as 'Intonaco di Calce Naturale' or 'Natural Beton 500 Venezia'. For internal use only.

PROCESSING

Apply with a metal trowel for a thickness of maximum 3 mm. After application, moisten and finish with a fine sponge float. It does not require mesh reinforcement.

SURFACE PREPARATION

The surface to be coated must be flat, coplanar and free of dust and dirt. Any traces of oils, greases, waxes, etc. must be removed beforehand. 'Malta Fine' can be applied on a base plaster previously moistened.

STORAGE

If protected from frost, it has an unlimited duration.

TECHNICAL DATA

Specific weight - Kg/m ³ dry	ca. 1.700 kg/m ³
Granulometry	< 0,6 mm
Yield	ca. 3-4 kg/m ²
Maximum thickness of application	ca. 3 mm
Vapour permeability - EN 1015-19	$\mu \leq 9$ (measured value)
Water absorption by capillarity - EN 1015-18	W0
Thermal conductivity - EN 1745	$\lambda = 0,45$ W/m·K (table value)
Class - UNI EN 998-1	GP-CSI-W0