

BIOMATTONE BA08

Air lime and Canapulo block

ITEM DESCRIPTION

Supply and installation of Biomattone® 8 cm thick, heat-insulating and breathable, made from a mix of Canapulo Grosso, Natural Dolomitic Binder and Probiotic Additive (density 310 kg/m³, thermal conductivity 0.044 W/mK - μ 4.5), as well as pre-mixed powder bedding mortar with Canapulo Fine 0-6mm, class M5. Suitable for internal and external infill masonry (non-load-bearing walls), external thermal insulation (ETICS) of external perimeter walls, internal insulation of perimeter walls, and partition walls.

Item includes labor, materials and transport.

Void-for-solid measurement (Vpp) up to 4.5 m².
For openings larger than this, a surface area of 4.5 m² will be calculated.

- Excludes scaffolding, accessory works (e.g. waterproofing of the first course);
- Excludes any supports for cantilevered masonry;
- Excludes any lintels with a span greater than 3 m;
- Excludes plaster and smoothing coat;
- Excludes painting.
- Excludes site layout works and graphic drawings.



NOTES

Tecnocanapa · Senini Srl reserves the right to modify and/or update the data provided in this document.
The updated version is available on the website <https://tecnocanapa-bioedilizia.it/>.
This document cancels and supersedes any previous version.