

INTONACO E CANAPA

ITEM DESCRIPTION

Supply and installation of Intonaco e Canapa approximately 1.5 cm thick, made of breathable mineral pre-mixed powder plaster based on natural hydraulic lime NHL 5 and Canapulo Fine 0-6mm; a specific formulation with high permeability to water vapour diffusion, selected siliceous and calcareous aggregates dosed in an appropriate 0-2 mm particle size curve, specific additives that improve performance in terms of workability, breathability and adhesion to substrates - $\mu < 6$ - thermal conductivity 0.45 W/mK - fire reaction class A1 - CE marked in accordance with standard EN 998-1, light hazelnut beige in colour, produced by calcining silica-rich marly limestone fired with coal at low temperature (below 1100°C), and pure carbonate sands, without the addition of hydraulic binders of any kind (clinker, cement, fly ash, blast furnace slag, etc.). Reinforcement with reinforced skim coat is recommended in the most stressed façade areas (for example around door and window openings, and material transitions).

Item includes labor, materials and transport.

Void-for-solid measurement (Vpp) up to 4.5 m². For openings larger than this, a surface area of 4.5 m² will be calculated.

- Excludes scaffolding, accessory works;
- Excludes finishing coat;
- Excludes painting.



NOTES

Tecnocanapa · Senini Srl reserves the right to modify and/or update the data provided in this document. The updated version is available on the website <https://tecnocanapa-bioedilizia.it/>. This document cancels and supersedes any previous version.