

BIOMATTONE BA30

Air lime and hemp shiv block

ITEM DESCRIPTION

Supply and installation of Biomattone® thickness

30 cm, heat-insulating and breathable, made from a blend of coarse hemp shiv, natural dolomitic binder and probiotic additive (density 310 kg/m³, thermal conductivity 0.044 W/mK - μ 4.5), together with a pre-mixed powder bedding mortar with fine hemp shiv 0-6mm, class M5. Suitable for internal and external infill masonry (non-load-bearing walls), external thermal insulation cladding for perimeter walls, internal insulation for perimeter walls, and partition walls.

Item inclusive of labor, materials and transport.

Gross measurement, openings not deducted (Vpp), up

to 4.5 m².

For larger openings, a surface area of 4.5 m² will be counted.

- Excluding scaffolding, ancillary works (e.g. waterproofing of the first course);
- Excluding any supports for cantilevered masonry;
- Excluding any lintels with a span greater than 3 m;
- Excluding plaster and smoothing coat;
- Excluding painting;
- Excluding layout markings and drawings.



NOTES

Tecnocanapa · Senini Srl reserves the right to modify and/or update the data provided in this document.

The updated version is available on the website <https://tecnocanapa-bioedilizia.it/>.

This document cancels and supersedes any previous version.